



- [1] CRILLY, M.S., SCHREINER, H.D. & GOURLEY, C.S. (1991). A simple field suction measurement probe. Proc 10th Afr Reg Conf Soil Mech & Found Engng, Maseru, 1, 291-298.
- [2] CHANDLER, R.J., CRILLY, M.S. & MONTGOMERY-SMITH, G. (1992). A low-cost method of assessing clay desiccation for low-rise buildings. Proc Instn Civ Engrs, Civ Engng, 92, 82-89.
- [3] CRILLY, M.S., DRISCOLL, R.M.C. & CHANDLER, R.J. (1992). Seasonal ground and water movement observations from an expansive clay site in the UK. Proc 7th Intl Conf Expansive Soils, Dallas, 1, 313-318.
- [4] CRILLY, M.S. & CHANDLER, R.J. (1993). A method of determining the state of desiccation in clay soils. BRE Information Paper No IP 4/93. Garston: BRE.
- [5] MARINHO, F.A.M, CHANDLER, R.J. & CRILLY, M.S. (1995). Stiffness measurements on an unsaturated high plasticity clay using bender elements. Proc 1st Intl Conf Unsaturated Soils, Paris, 2, 535-540.
- [6] DRISCOLL, R.M.C., CRILLY, M.S. & BUTCHER, A.P. (1996). Foundations for low-rise buildings. The Structural Engineer, 74, 179-185.
- [7] SKINNER, H.D., CRILLY, M.S. & CHARLES, J.A. (1998). Numerical models for the design of shallow foundations for low-rise buildings. Proc 4th Eur Conf Num Meth Geotech Engng, Udine, 655-664.
- [8] CHOWN, R.C. & CRILLY, M.S. (2000). Performance of a semi-rigid raft foundation on soft ground under vertical load. Ground Engineering, 33(3), March, 36-40.
- [9] CRILLY, M.S. & DRISCOLL, R.M.C. (2000). The behaviour of lightly loaded piles in swelling ground and implications for their design. Proc Instn Civ Engrs, Geotech Engng, 143, 3-16.
- [10] DRISCOLL, R.M.C. & CRILLY, M.S. (2000). Subsidence damage to domestic buildings: lessons learned and questions remaining. Foundation for the Built Environment Report 1. London: CRC Ltd.
- [11] CRILLY, M.S. (2001). Analysis of a database of subsidence damage. Structural Survey, 19(1), 7-14.